




PRODUCT BROCHURE · BENCHMARK SCIENTIFIC

IPD4400 BenchMasher 400

5 models inside · Life Science · Homogenizers & Cell Lysis



QUICK VIEW — SERIES AT A GLANCE

5 models in this document from Benchmark Scientific. Full specifications inside.

MODELS IN THIS DOCUMENT

IPD4400-E · IPD4400-B400F1 · IPD4400-B400F2 ·
IPD4400 · IPD4400-B400

SHIP WEIGHT

42 lb

VOLTAGE

120 V or 220 V — confirm plug type at order

SOURCING

Authorized U.S. distributor

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours



BENCHMASHER™

LABORATORY PADDLE BLENDER



- + **Contamination free mixing/homogenizing of samples**
- + **Touch screen control with variable mixing speed and temperature control**
- + **Adjustable stroke length to accommodate samples of various types**
- + **Built in UV light for chamber decontamination**

The BenchMasher provides fast and effective mixing, ensuring consistent homogenization. It is ideal for preparation of samples where eliminating contamination is critical, such as pathogen and microbial detection in food and water filters. However, its use is not limited to those areas – the BenchMasher has applications anywhere larger solid samples need broken down or products such as powders and polymers need mixed.

Samples up to 400ml are conveniently loaded in the sterile blender bags which are sealed upon closing the door. Mixing paddles rapidly strike the bags, producing thorough mixing and homogenization without ever directly contacting the sample. Programming is user friendly - mixing speed and cycle time are easily adjusted on the large, full color touch screen. Paddle position can be adjusted to ensure efficient processing of samples. For applications requiring thermal regulation (such as Trichinella testing in meat) the chamber can be heated and maintained at temperatures up to 65°C.

The door is removable for access to the chamber and stainless steel mixing paddles. Each paddle includes a convenient rubber cover that is easily removed or replaced. A UV light (254nm) is built into the chamber and can be activated at any time to perform complete decontamination.

Ordering Information

IPD4400* BenchMasher™ 400 Paddle Blender

Blender Bag Accessories:

IPD4400-B400 400ml x 60µm, 300 x 180mm, 500pk
IPD4400-B400F1 400ml x 70µm with lateral (side) nylon filter, 300 x 190mm, 500pk
IPD4400-B400F2 400ml x 70µm with full nylon filter, 300 x 190mm, 500pk

*120V. For 220V, add-E to catalog number

Technical Data

Speed/Increments	3 to 12 SPS (strokes per second)
Timer:	1 sec. to 100 min. or cont.
Paddle Distance:	0 to 50mm
Temp. Range:	RT - 65°C
Ambient operating temp.	2°C to 35°C
Bag Size:	16-18cm(W) x 25-30cm(H)
UV Bulb:	254nm
Dimensions (WxDxH)	9x16.5x13 in / 23x42x33 cm
Weight	42 lbs / 19kg
Electrical	120V 50Hz or 230V 60Hz, 220W
Warranty	2 years

Benchmark 
INDUSTRIAL Products

PO Box 709 - Edison, NJ 08818
Phone: 908-769-5555 - Fax: 732-313-7007
Web: www.BenchmarkScientific.com
Email: Info@BenchmarkScientific.com