



PRODUCT BROCHURE · BENCHMARK SCIENTIFIC

S1005 MiniMag Stirrer No Pricing Brochure

2 models inside · Mixing & Agitation · Hotplates & Stirrers



QUICK VIEW — SERIES AT A GLANCE

2 models in this document from Benchmark Scientific. Full specifications inside.

MODELS IN THIS DOCUMENT

S1005 · S1005-E

SHIP WEIGHT

1 lb

VOLTAGE

100 or 240 V, 50–60 Hz

SOURCING

Authorized U.S. distributor

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours



MiniMAG™

Mini Magnetic Stirrer



- Mini sized, less than 5" wide
- Adjustable speed control, 100 to 1500rpm
- Effectively mixes volumes up to 1.5L



Technical Data:

Speed Range:	100 to 1500 rpm
Platform Dimensions:	3.4 x 3.4 in. / 8.5 x 8.5 cm
Operating Temp. Range:	+4 to +45°C
Max. Stir Bar:	30 mm
Dimensions: (WxDxH):	4.7 x 4.7 x 1.2 in. 12 x 12 x 3 cm
Weight:	0.45 lbs. (0.2kg)
Electrical:	100 to 240VAC, 50-60Hz 2W (5V DC power supply)
Warranty:	1 year

With a square footprint of under 5 inches, the MiniMag™ is the most compact stirrer in the Benchmark line. Despite its modest dimensions, the 3.4 inch square work surface accepts a wide variety of beakers, flasks, bottles and other laboratory vessels for stirring volumes as large as 1.5 liters.

The stirring speed is continuously adjustable from 100 to 1500rpm. For temperature sensitive samples, the MiniMag is incubator and cold-room safe for use from +4°C to +45°C.

Ordering Information:

S1005* MiniMag™ Mini Magnetic Stirrer

*Includes US plug. For EU Plug, please add (-E).

Benchmark
Scientific

Benchmark Scientific Inc.
PO Box 709 Edison, NJ 08818
Phone: 908-769-5555
Fax: 732-313-7007
Web: www.BenchmarkScientific.com
Email: Info@BenchmarkScientific.com