



LLS QUICK VIEW · BENCHMARK SCIENTIFIC

Z216-MK Refrigerated MicroCentrifuge, 120V

SKU Z216-MK · Centrifuges · Refrigerated Centrifuges

The Z216-MK is the refrigerated sibling of the Z216-M: same 15,000 rpm / 21,379 × g performance ceiling, same 24-position fixed-angle rotor catalog,



TECHNICAL SPECIFICATIONS

VOLTAGE

120 V / 50 – 60 Hz

CAPACITY

Up to 30 × 1.5 / 2.0 mL microtubes (rotor-dependent); 4 ×...

REFRIGERATION

CFC-free; pre-cooling program; standstill cooling

MAX. SPEED

15,000 rpm

PROGRAM MEMORY

99 saved runs (including rotor type and temperature)

DIMENSIONS (W × H × D)

11 in × 10.2 in × 14.6 in (28 × 26 × 37 cm)

EUROPEAN POWER CONFIGURATION

Available upon request

LIST PRICE

\$7,297.23

TEMP RANGE

-20°C to +40°C (1°C increments, °C or °F selectable)

MAX SPEED

200 – 15,000 rpm

MAX. RCF

21,379 × g

RUNNING TIME

10 s to 59 min 50 s (10 s increments); 1 min to 99 h 59...

SAFETY STANDARDS

IEC 61010

NOISE LEVEL

< 60 dBA at max. speed

SHIPPING WEIGHT

90 lb (41 kg)

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours

