



PRODUCT BROCHURE · HAIER BIOMEDICAL

(115V 60HZ) Pharmacy Refrigerator HYC 940 2022.09.16 ☐☐

7 models inside · Cold Storage · ULT Freezers



QUICK VIEW — SERIES AT A GLANCE

7 models in this document from Haier Biomedical. Full specifications inside.

MODELS IN THIS DOCUMENT

DW-86L100J · DW-86L51J · HLR-310FL ·
HYC-1378 · HYCD-469A · ...

SOURCING

Authorized U.S. distributor

SHIP WEIGHT

584 lb

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours





HYC-940

Pharmacy Refrigerator

Scope of Application :

The pharmacy refrigerator is suitable for pharmacies, drug stores, pharmaceutical companies, hospitals, clinics and other pharmaceutical storage areas such as storage and logistics.

Innovative Design

- High Accuracy Temperature Control
- Interior LED
- Lockable Design

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
Tel: +86-0532-88935593
E-mail: inquiry@haierbiomedical.com
Website: www.haiermedical.com



Haier Biomedical
International



Haier Biomedical
International



@haiermedicalint



Haier Biomedical
International



Haier Biomedical
International

Product Advantages



Six Alarm Functions

High/low temperature, remote alarm, power failure, sensor error, low battery, door ajar



Air Cooling, Auto Defrost

Better cabinet temperature uniformity, auto defrost



Self Closing Door

Energy conserving, maintains temperature uniformity to protect valuable samples



Adjustable Shelves

The shelves are adjustable to any height to fulfill different requirements



Heated Double Pane Glass Door

Clear display of stored products without condensation at 32°C and 85% relative humidity condition



Specifications



Model			HYC-940	
Technical Data	Cabinet Type		Upright, double glass door	
	Climate Class		N	
	Cooling Type		Forced air cooling	
	Defrost Mode		Auto	
	Refrigerant		HC	
	Noise (dB(A))		43	
Performance	Temp Range (°C)		2-8	
Control	Controller		Microprocessor	
	Display		LED	
Electrical Data	Power Supply (V/Hz)		115/60	
	Power (W)		1300	
	Electrical Current (A)		11.5	
Dimensions	Capacity (L/Cu.Ft)		890/31.4	
	Net/Gross Weight (approx)	kg	227/279	
		lbs	500.4/615.1	
	Interior Dimensions (W*D*H)	mm	1030*590*1425	
		in	40.6*23.2*56.1	
	Exterior Dimensions (W*D*H)	mm	1130*755*1980	
		in	44.5*29.7*78.0	
	Packing Dimensions (W*D*H)	mm	1250*850*2130	
		in	49.2*33.5*83.9	
Functions	ContainerLoad (20'/40'/40'H)		8/18/18	
	High/Low Temp		Y	
	Remote Alarm		Y	
	Power Failure		Y	
	Sensor Error		Y	
	Low Battery		Y	
	Door Ajar		Y	
Accessories	Caster		Y	
	Foot		Y	
	Porthole		Y	
	Shelves/Basket		12/-	
	Temperature Recorder		Optional	
	USB Interface		Optional	
Others	Certification		UL	

*Haier Biomedical reserves the right to change products and specifications without prior notice.