



PRODUCT BROCHURE · HAIER BIOMEDICAL

# CO2 Incubator Brochure2

6 models inside · Thermal Processing · Incubators & Ovens



QUICK VIEW — SERIES AT A GLANCE

6 models in this document from Haier Biomedical. Full specifications inside.

MODELS IN THIS DOCUMENT

HEPA-HCP · TRAY-HCP · HCP-258B · ROLLER-80B · HCP-168B · HCP-80B

SOURCING

Authorized U.S. distributor

SHIP WEIGHT

209 lb

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours



Specifications

| Model                 |                                                                              |     | HCP-80                                          | HCP-168           | HCP-258           |
|-----------------------|------------------------------------------------------------------------------|-----|-------------------------------------------------|-------------------|-------------------|
| Type                  |                                                                              |     | Air Jacket                                      | Air Jacket        | Air Jacket        |
| Construction          | Chamber Volume (L)                                                           |     | 80                                              | 170               | 258               |
|                       | Interior Chamber                                                             |     | Stainless Steel                                 |                   |                   |
|                       | Exterior Chamber                                                             |     | Cold-rolled Steel Powder Coated                 |                   |                   |
|                       | Access Port                                                                  |     | 35mm Diameter                                   |                   |                   |
|                       | Data Outputs                                                                 |     | Remote Alarm Contacts, USB, and Optional 4-20mA |                   |                   |
| Dimensions            | Net/Gross Weight (approx)                                                    | kg  | 75/100                                          | 110/140           | 135/170           |
|                       |                                                                              | lbs | 165/220                                         | 242.5/308.6       | 297/374           |
|                       | Interior Dimensions (W*D*H)                                                  | mm  | 400*420*490                                     | 490*560*650       | 570*610*745       |
|                       |                                                                              | in  | 15.7*16.5*19.3                                  | 19.3*22*25.6      | 22.4*24.0*29.3    |
|                       | Exterior Dimensions (W*D*H)                                                  | mm  | 625*684*735                                     | 714*812*887       | 794*867*985       |
|                       |                                                                              | in  | 24.6*26.9*28.5                                  | 28.1*32*34.9      | 31.3*34.1*38.8    |
|                       | Packing Dimensions (W*D*H)                                                   | mm  | 695*755*915                                     | 760*840*1050      | 865*940*1135      |
|                       |                                                                              | in  | 27.3*29.7*36.0                                  | 29.9*33.1*41.3    | 34.0*37.0*44.7    |
| Shelves               | Dimensions (W*D)                                                             | mm  | 380*300                                         | 470*434           | 550*484           |
|                       | Number Standard/Maximum                                                      |     | 3/7                                             | 3/11              | 3/13              |
|                       | Max.load Per Shelf/Total Load                                                | kg  | 10/30                                           | 10/30             | 10/30             |
|                       | Construction                                                                 |     | Perforated, Adjustable                          |                   |                   |
| Electrical            | Rated Voltage Power Supply (V/Hz)                                            |     | 220/50                                          | 220/50            | 220/50            |
|                       | Nominal Consumption (kw) (Steri-run)                                         |     | 0.07 (0.9)                                      | 0.095 (1.4)       | 0.12 (1.6)        |
| Control               | Controller                                                                   |     | Microprocessor                                  | Microprocessor    | Microprocessor    |
|                       | Display                                                                      |     | 7 "LCD Screen                                   | 7 "LCD Screen     | 7 "LCD Screen     |
| CO <sub>2</sub>       | Control                                                                      |     | ±0.1%                                           | ±0.1%             | ±0.1%             |
|                       | Range                                                                        |     | 0-20%                                           | 0-20%             | 0-20%             |
|                       | Alarm Range                                                                  |     | ±0.5%                                           | ±0.5%             | ±0.5%             |
|                       | Inlet Pressure                                                               |     | 12-17Psi (0.8-1.2 Bar)                          |                   |                   |
|                       | Gas Purity                                                                   | %   | Min.99.5 or Medical Quality                     |                   |                   |
|                       | Sensor                                                                       |     | IR                                              | IR                | IR                |
|                       | Recovery Time at 5vol.-%/CO <sub>2</sub> for a 30 Second Door Opening* (min) |     | 4                                               | 4                 | 4                 |
|                       | CO <sub>2</sub> Inlet Filter (µm)                                            |     | <0.2                                            | <0.2              | <0.2              |
| Alarms                | High/Low Temperature                                                         |     | Y                                               | Y                 | Y                 |
|                       | Remote Alarm                                                                 |     | Y                                               | Y                 | Y                 |
|                       | Excessive CO <sub>2</sub> Concentration                                      |     | Y                                               | Y                 | Y                 |
|                       | Water Shortage                                                               |     | Y                                               | Y                 | Y                 |
|                       | Door Ajar                                                                    |     | Y                                               | Y                 | Y                 |
| Temperature Parameter | Control (°C)                                                                 |     | ±0.1                                            | ±0.1              | ±0.1              |
|                       | Range                                                                        |     | Range 3°C Above Ambient to 55°C                 |                   |                   |
|                       | Uniformity (°C)                                                              |     | ±0.3                                            | ±0.3              | ±0.3              |
|                       | Ambient Range (°C)                                                           |     | 18-32                                           | 18-32             | 18-32             |
|                       | Sensor                                                                       |     | PT1000                                          | PT1000            | PT1000            |
|                       | Recovery Time at 37°C for a 30 Second Door Opening* (min)                    |     | 4                                               | 4                 | 4                 |
| Sterilization Cycle   | Cycle Temperature                                                            |     | 180°C on all Internal Surfaces                  |                   |                   |
|                       | Cycle Duration                                                               |     | Under 12 Hours                                  | Under 12 Hours    | Under 12 Hours    |
| Humidity              | RH (Relative Humidity)                                                       |     | Setting 37°C ≥90%                               | Setting 37°C ≥90% | Setting 37°C ≥90% |
|                       | Humidity Reservoir                                                           |     | Max.1.3L/Min 0.5L                               | Max.3L/Min 0.5L   | Max.3.6L/Min 0.5L |
| Optional              | Hepa Filter                                                                  |     | Y                                               | Y                 | Y                 |
|                       | Pressure Reducing Valve                                                      |     | Y                                               | Y                 | Y                 |
|                       | RS485                                                                        |     | Y                                               | Y                 | Y                 |
|                       | 4-20mA                                                                       |     | Y                                               | Y                 | Y                 |
|                       | The Cylinder Switch                                                          |     | Y                                               | Y                 | Y                 |
| Certification         |                                                                              |     | CE                                              | CE                | CE                |

Product appearance and specifications are subject to change without notice

CO<sub>2</sub> Incubator  
HCP-80/168/258

Product Features

- Uniform and Stable Temperature
- Precise CO<sub>2</sub> Concentration
- 180°C Dry-heat Sterilization
- IoT APP Available for Real Time Monitoring (optional)



Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,  
Qingdao, 266109, P.R. China  
Tel: +86-0532-88935593  
Website: www.haiermedical.com



## CO2 Incubator

Haier Biomedical IoT enabled CO<sub>2</sub> incubator with 180°C dry heat sterilisation provides a safe, reproducible growth environment for cell cultures.

### IR Sensitive Control of CO<sub>2</sub> Concentration

The new IR sensor with high temperature resistance of 190°C is based on the NDIR measurement principle and uses a silicon MEMS transmitter to replace the traditional light source. It can withstand more than 300 dry heat sterilization cycles with a service life of up to 15 years and control accuracy of  $\pm 0.1\%$ . German IR infrared sensing technology, zero drift, without need for calibration, drift less than 0.3% within 2 years.



### 7-inch Touchscreen

It displays CO<sub>2</sub> concentration and temperature data in real time. 15 years of data can be exported via USB.

### Inner Door

It ensures the sealing inside the cabinet.

### Outer Door

The heated outer door prevents the condensation of the inner door.

### Precise Temperature Control

With six-sided heating based on fuzzy PID control, it has internal dual PT1000 high precision sensors.



6-sided heating sketch

### 304 Stainless Interior



### Adjustable Feet

It can be double stacked.

### 180°C Dry-heat Sterilization

All internal components do not need to be disassembled and do not need separate autoclave sterilization to prevent secondary pollution. Do not need consumables, one-click sterilization. German INFRARED CO<sub>2</sub> sensor, NDIR light source technology drift < 0.3% within two years. It can withstand sterilization at 180°C with no disassembly and no manual calibration.


### Internal Partition

Safety anti-slip design of pull out shelves.




## Precise and Accurate Temperature Control

Controls the temperature precisely, within  $\pm 0.1^\circ\text{C}$ , with six-sided heating based on the fuzzy PID control principle, to provide a stable temperature to ensure the normal growth of cells throughout their life cycle.




Uniformity of 27 measuring points  $\leq \pm 0.3^\circ\text{C}$




Central consistency point  $\leq \pm 0.1^\circ\text{C}$

## Precise CO<sub>2</sub> Concentration Using New IR Sensor Control Technology

Haier Biomedical's new IR Sensor technology uses NDIR measurement principles and withstands high temperatures of 190°C. The silicon MEMS transmitter can carry out more than 300 dry heat sterilization cycles to extend the service life to 15 years. Built-in temperature and humidity compensation technology reduces the impact of changes of humidity and temperature without the need for calibration after the high temperature sterilization. Five point calibration yields a higher measuring accuracy, sensitivity with less drift.



Silicon-based mems transmitter



Sketch of drift less than 0.3%

## Fast Environment Recovery for Optimal Cell Growth

Adopting active air flow control technology, based on the fuzzy PID control principle, the parameters can be restored without overshoot. After opening the door for 30 seconds, the temperature and CO<sub>2</sub> concentration can be quickly restored within 4 minutes. Even if multiple users share a CO<sub>2</sub> incubator and frequently open and close the door, the stability and uniformity of the incubator can be ensured.






Illustration of purified airflow



Temperature recovery curve (door open for 30s)




CO<sub>2</sub> concentration recovery curve (door open for 30s)

180°C Dry-Heat Sterilization Technology Minimises Contamination

Easy and effective sterilization of microorganisms including bacteria, fungi and microplasma with strong resistance, at 180°C high temperatures without the need for consumables. Simply press the "sterilization key" to activate and complete the sterilization process automatically in just 12 hours.

Delivers sterility level within the chamber of all surfaces to meet WS/T367-2012 standards.

All components are sterilized during the process, there is no need to disassemble internal components (including CO<sub>2</sub> sensors) and decontaminate separately, thus avoiding secondary pollution.



**Sterilization Temperature Profile**

Forty-seven points were tested in the working chamber, including glass inner doors and partitions. All regions reached 180°C and maintained for 2 hours.



**Ultraviolet disinfection**

Cells exposed to bacterial environment



**90°C hygrothermal disinfection**

Cells exposed to bacterial environment



**180°C dry-heat sterilization of haier CO<sub>2</sub> incubator**

Pollution-free cell growth environment


High Efficiency Microbial Filter



The CO<sub>2</sub> inlet is equipped with a high-efficiency microbial filter, with 99.99% filtration efficiency for particles larger than or equal to 0.2µm in diameter. It can effectively filter bacteria and dust particles in CO<sub>2</sub> gas line to ensure the safety of experimental results.

Easy to Clean Interior

The working chamber is plasma electro polished, stamped stainless steel with wide-arc, laser welded corners. Bracketless shelving design ensures is quick and easy to clean.



Interactive Intelligent Display with Easy Touch Operation

Touch-sensitive screen with rapid sensing even in rubber gloves. Green indicates normal operational parameters while a red warning display indicates abnormal making it easy to view data at a glance. A red warning display and audible buzzer will alarm when water level is low.



Home screen red warning



Real-time display of operation data real-time display of temperature, CO<sub>2</sub> concentration and O<sub>2</sub> concentration, and the data during the culture cycle can be viewed at any time.



Announcement function designed for multiple persons to use the same incubator make clear to all users on important things.



Operation mode clear management authority: three-level of authority to ensure the security of data.

Realtime Monitoring via Optional IoT Module



IoT module with multi-screen interaction, provides real-time upload of set parameters, operation parameters, operation curves, records and event records through the IoT cloud platform. The operation of incubator can be monitored anytime anywhere through mobile APP or computer terminal. The alarm function and service function are available with just the touch of a button.

Anti-Condensation Heating System to Reduce Pollution Risk

The door on the CO<sub>2</sub> incubator radiates heat to the inner glass door, effectively preventing the glass door from forming condensation. The possibility of microbial contamination caused by the condensate water is eliminated.

Intelligent Control of Circulating Air Maintains Uniformity

Automatically adjusts the circulation of the air flow, optimising the air flow to avoid air volatilization of samples and ensuring proper uniformity throughout the chamber.

Comprehensive Safety Alarm System

The system ensures the safety of experiments and processes by utilizing an independent temperature alarm system including a sound light and remote reminder. Other alarms include CO<sub>2</sub> concentration, door ajar and water shortage.


Thoughtful Design with Attention to Details



Safe anti-slip design of pull out shelves.



Convenient drainage design




Active heat pipe condensation technology with condensate water directly return to reservoir.



Data traceable for 15 years with large storage capacity and data exportable through usb.

CAD Dimensions



Optional Accessories

| Name               | Picture |
|--------------------|---------|
| Relief Valve       |         |
| HEPA Filter        |         |
| HEPA Filter Cover  |         |
| Stacking Frame     |         |
| Internal partition |         |
| Roller base        |         |

| Name                              | Picture |
|-----------------------------------|---------|
| Water Tray                        |         |
| Oxygen Sensor (only for HCP-168)  |         |
| Solenoid Valve (only for HCP-168) |         |
| 6 Inner Door (only for HCP-168)   |         |
| 3 Inner Door (only for HCP-168)   |         |