


-40°C Smart Frequency Conversion Freezer

DW-40L959BP



Scope of Application:

Used in the blood banks, hospitals, disease control centers, research institutes, electronic, chemical and other industries, cryopreservation of plasma, biologics and other products, and cold tests for components and materials.



High-efficiency and Energy-saving
Compressor and System



Green and Environmental Friendly



Superior Temperature Uniformity



Low Sound Level

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
E-mail: inquiry@haierbiomedical.com
Website: www.haiermedical.com



Haier Biomedical
International



Haier Biomedical
International



@haiermedicalint



Haier Biomedical
International



Haier Biomedical
International



Product Features



High-efficiency and Energy-saving Compressor and System

Optimized refrigeration system with a high efficiency inverter compressor to reduce energy consumption.



Low Sound Level

Noise level less than 42dB, providing a more comfortable environment.



Green and Environmental Friendly

Hydrocarbon refrigerant, energy saving and environmental protection, built with urethane foam insulation complies with European ROHS regulation.



Superior Temperature Uniformity

The temperature uniformity is $\pm 3^{\circ}\text{C}$ with the setting temperature of -40°C .



Ergonomic Design



Microprocessor-controlled System

Microprocessor control, with temperature display precision at 0.1°C . Internal temperature is adjustable from -20°C to -40°C .



Super-large Capacity

Large capacity (700 2-inch box) to accommodate the multiple storage needs.



Safe and Secure

Equipped with key lock, padlock, optional electronic lock, providing multiple safeguards for sample safety.



Multiple Alarm Functions

Including high/ low temperature, sensor error, power failure, low battery, high ambient, and door ajar alarms. Alarm mode is sound and flash. And the remote alarm interface is available.



Configuration

Standard: RS485 interface, 2 coated steel wired shelves.

Optional: Temperature recorder, Printer, USB interface, NCF, 10-inch touch screen, IoT module, Stainless steel shelves, Blood basket.

Product Parts

Document holding compartment for storing size A4 paper and pens

NFC clocking-in function (optional)

Optional USB port allows users to download temperature data saved up to 10 years for compliance and auditing purposes

Casters and leveling legs for ease of maneuvering and positioning




Shelf height can be adjusted according to the size of the stored articles, so as to realize the efficient use of large space in the cabinet (SUS304 stainless shelves as optional)

Pressure equalization port for easy door opening

Ergonomic handle design: easy access to storage space, built in lock and padlock features

Two standard portholes allow ease of temperature testing

Product Dimension Drawings



Ramark

W0=Total Width

W1=Freezer Width

W2=Inner Cabinet Width

W3=Inner Cabinet Shelf Width

D0=Total Depth

D1=Inner Cabinet Depth

D2=Inner Cabinet Shelf Depth

H0=Total Height

H1=Inner Cabinet Height

Model	Code	W0	W1	W2	W3	D0	D1	D2	H0	H1
DW-40L959BP		1296mm	1196mm	1016mm	1008mm	998mm	716mm	641mm	1980mm	1310mm



Specifications

Model			DW-40L959BP
Technical Data	Cabinet Type		Upright
	Climate Class		SNN
	Cooling Type		Direct Cooling
	Defrost Mode		Manual
	Refrigerant		HC
	Sound Level (dB(A))		42
Performance	Cooling Performance (°C)		-40
	Temperature Range(°C)		-20~-40
Control	Controller		Microprocessor
	Display		LED
Electrical Data	Power Supply (V/Hz)		100-230/50/60
	Electrical Current (A)		7.9
Dimensions	Capacity (L/Cu.Ft)		959/33.9
	Net/Gross Weight (approx)	(kg)	350/400
		(lbs)	771.6/881.8
	Interior Dimension (W*D*H)	(mm)	1016*716*1310
		(in)	40.0*28.2*51.6
	Exterior Dimension (W*D*H)	(mm)	1296*998*1980
		(in)	51.0*39.3*78.0
	Packing Dimension (W*D*H)	(mm)	1358*1098*2127
		(in)	53.5*43.2*83.7
Alarms	Container Load (20'/40'/40'H)		8/16/16
	High/Low Temperature		Y
	Remote Alarm		Y
	Power Failure		Y
	Sensor Error		Y
	Low Battery		Y
	High Ambient Temperature		Y
	Dirty Condenser		N
Accessories	Door Ajar		Y
	Caster		Y
	Leveling Feet		Y
	Porthole		Y
	Drawers/Inner Doors		N/3
	Adjustable Shelves		Y (2)
	USB Interface		Optional
	RS485		Y
	NFC		Optional
Other	Temperature Recorder		Optional
	Certificate		CE, UL

*Haier Biomedical reserves the right to change products and specifications without prior notice.

