



PRODUCT BROCHURE · HAIER BIOMEDICAL

Haier Spark-Free Explosion-Proof Laboratory Refrigerator +3 to +16°C , 310 L / 115V

SKU HLR-310FL · Cold Storage · Refrigerators



QUICK VIEW

The Haier HLR-310FL is a spark-free, ATEX-certified explosion-proof laboratory refrigerator for storing flammable and volatile reagents safely, with

SOURCING

**Authorized U.S.
distributor**

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours





HLR-310FL

Laboratory Refrigerator

Scope of Application:

This product is suitable for storing inflammable and explosive reagents in laboratories of universities and scientific research institutes

Innovative Design

- Explosion Proof Fan
- Setting Temperature Range +3°C to +16°C
- Energy Star® Certified
- 360° Explosion Proof Interior
- ATEX Certified

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
Tel: +86-0532-88935593
E-mail: inquiry@haierbiomedical.com
Website: www.haiermedical.com



Haier Biomedical
International



Haier Biomedical
International



@haiermedicalint



Haier Biomedical
International



Haier Biomedical
International

Product Advantages

- **ATEX II C-T6 EU Explosion Proof Certified**

Our 360° all-around explosion proof system uses an antistatic liner, gasket and explosion proof fan motor. It is also equipped with an overcurrent and overvoltage protection system. All components within the unit are earthed to ensure static is discharged safely.
- **Setting Temperature Range +3°C to +16°C**

The setting temperature can be adjusted within the range of 3°C to 16 °C to meet multi-temperature storage requirements. With precise control, the internal temperature variation can be kept within 3°C for great temperature uniformity.
- **Energy Efficient Design**


The hydrocarbon cooling system doubles the cooling efficiency and saves half the energy when compared to traditional refrigerants. In addition, the cabinet is fitted with an energy saving explosion proof fan.
- **Safe and Secure**

Built-in lock and adapter kit to allow users to add a padlock. Lockable control panel to prevent anyone turning off the unit by mistake or adjusting the temperature by accident.
- **Clear and Complete Alarm System with One Key Search**

Multiple alarms and data function which allows users to check and save historical data, useful and convenient for laboratory inspection processes.
- **Multiple Alarms**

The refrigerator comes with high/low temperature alarm, door ajar alarm, sensor error alarm.


Product Introduction




Temperature Curve



Cooling Down Curve




Stability Curve



— Internal Temperature
— Ambient Temperature

Product Dimensions



Specifications



Model			HLR-310FL
Technical Data	Type		Upright
	Climate Class		N
	Cooling Type		Forced Air Cooling
	Defrost Mode		Auto
	Refrigerant		R600a, 40g
	Sound Level (dB(A))		43
Performance	Temperature Range (°C)		3-16 Adjustable
	Ambient Temperature (°C)		16-32
Control	Controller		Microprocessor
	Display		LED
Electrical Data	Power Supply (V/HZ)		115/60
	Power (W)		210
	Electrical Current (A)		2.5
Dimension	Capacity (L/Cu.Ft)		310/10.9
	Net/Gross Weight (approx)	kg	72/83
		lbs	158.7/183
	Interior Dimensions (W*D*H)	mm	560*500*1290
		in	22.0*19.7*50.8
	Exterior Dimensions (W*D*H)	mm	605*598*1840
		in	23.8*23.6*73.6
	Packing Dimensions (W*D*H)	mm	660*670*2020
		in	26*26.4*79.5
Alarms	Container Load (20'/40'/40'H)		24/51/51
	High/Low Temperature		Y
	Sensor Error		Y
	Door Ajar		Y
Accessories	Caster		4
	Foot		2
	Shelves/Baskets		4/0
	Water tray		1
	Padlock Adapter Kit/Quantity		1
	Built-in Key Door Lock/Quantity		1
Others	Certification		UL, ATEX, Energy star

*Haier Biomedical reserves the right to change products and specifications without prior notice.