



SPECIFICATION SHEET · SCIENTEMP

Scientemp Model 80-12 Chest Freezer with 12 Cu. Ft. Capacity

SKU 80-12-BASE · Cold Storage · ULT Freezers



QUICK VIEW

Shop the Scientemp Model 80-12 Chest Freezer with 12 Cu. Ft. Capacity (80-12-BASE). (Ultra Low Temp) $\sim -40^{\circ}\text{C}$ To $\sim -80^{\circ}\text{C}$ range. Authorized distributor...

VOLTAGE

115V, 230V

TEMPERATURE RANGE

**(Ultra Low Temp)
 $\sim -40^{\circ}\text{C}$ to $\sim -80^{\circ}\text{C}$**

SIZE / CAPACITY

12 Cu. Ft. / 340L

STYLE

Chest

SHIP WEIGHT

539 lb

SOURCING

**Authorized U.S.
distributor**

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours





ScienTempTM

Low Temperature Freezer



Versatile Design—Standard Models or we can custom design one that meets your needs

Safety & Easy Access - Counter-balanced lid with magnetic gasket. Brushed aluminum and thermoplastic tubular handle with separate Keyed Hasp Lock. Inner Styrofoam Sub-lids are included for additional

Safe & Economical Insulation— Our freezers are insulated using environmentally safe PFAS-free Ecofoam Polyurethane Foam.

CFC Free Refrigerant - All products are manufactured using CFC-free, non-toxic, non-combustible and non-ozone depleting refrigerant. Compressors are permanently lubricated and hermetically sealed for easy maintenance.

Sturdy Construction - Our cabinets are welded steel with a textured exterior / smooth interior powdercoat finish.

Temperature Display - Digital readout displays internal temperature and set point in either degrees Centigrade or Fahrenheit.

Standard Visual / Audible Alarm System - Alarm monitoring system indicates power on and displays visual / audible warning of rise in temperature and/or power failure.

Casters / Locking Lid - Locking 3" heavy duty swivel type casters and Key-Locking counterbalanced lid with magnetic gasket.

Optional Accessories

- 6" Temperature Chart Recorder
- Calgrafix Software
- Voice Pager / Dialer
- Explosion Proofing
- Internal Heater and Internal Fan
- Stainless Steel Interior and / or Exterior
- Observation Window
- Ramp / Soak Control
- Access Ports (1", 2" or 4" are available)
- CO2 and LN2 Back-Up Systems

Model 80-12 Low Profile

Exterior Dimensions	40"H x 78"W x 32.25"D
Interior Dimensions	25"H x 49"W x 17"D
Temperature Range	-45°C to -80°C / -50°F to -112°F
Capacity	12 cubic feet
Insulation	Polyurethane
Door	Keyed Hasp Lock
Casters	(4) 3" Locking
Temperature Controller	Digital Display
Alarm	Visual and Audible

**Exterior height includes casters

**Depth measurement includes hinges and handle.

Refrigeration

Compressor	1/2 hp
Refrigerant	R-513A High Stage / R-508B Low Stage
Voltage Options	115/60/1 - 230/60/1 - 230/50/1
Refrigerant Control	Capillary Tube
Evaporator	Cold Wall
Defrost	Manual
Air Circulation	Gravity
Running Amps	12 amps (115V) 6 amps (230V)

Scientemp Corporation 3565 S. Adrian Hwy Adrian, MI 49221 Ph: 517-263-6020

www.scientemp.com

January 2025