



LLS QUICK VIEW · YAMATO SCIENTIFIC

Muffle Furnace with Communication Port 3.75 L, 115V

SKU FO-201CR · Thermal Processing · Muffle Furnaces

The Yamato FO-201CR is a 3.75 L benchtop muffle furnace reaching 1150 °C with ± 2 °C control accuracy at top temperature, on a low-mass ceramic-fiber



TECHNICAL SPECIFICATIONS

VOLTAGE

115V, 50/60 Hz (base FO200: 100V AC single phase, 16 A)

EXTERNAL DIMENSIONS

346 × 405 × 516 mm (W×D×H)

HEATER

Iron-chrome wire (Kanthal AF), 1.5 kW

WEIGHT

Approx. 30 kg

CLASS / TIER

Capital — high-temperature furnace / Tier 2

SAFETY DEVICES

Earth-leakage/circuit breaker, thermal fuse...

SETTING / DISPLAY

Digital setting; digital display

OPERATION FUNCTIONS

Fixed temperature; timer (auto-stop, auto-start); program...

TEMP RANGE

100 to 1150 °C

INTERNAL DIMENSIONS

100 × 250 × 150 mm (W×D×H)

SENSOR

R thermocouple (W sensor)

COOLING FAN

Axial fan motor

CONTROL SYSTEM

PID control by VS4 controller

MODEL / CAPACITY

Yamato FO200 (FO-201CR, comm-port gen) — approx. 3.75 L

ADJUSTMENT ACCURACY

± 2 °C (at 1150 °C)

ADDITIONAL FUNCTIONS

Lock function; auto recovery after power failure...

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours

