



LLS QUICK VIEW · YAMATO SCIENTIFIC

## Muffle Furnace with Communication Port 3.75 L, 220V

SKU FO-211CR · Thermal Processing · Muffle Furnaces

The Yamato FO-211CR is a 3.75 L benchtop muffle furnace reaching 1150 °C with  $\pm 2$  °C control accuracy at top temperature, on a low-mass ceramic-fiber



### TECHNICAL SPECIFICATIONS

#### VOLTAGE

220V, 50/60 Hz (200V amperage not documented at this...

#### EXTERNAL DIMENSIONS

346 × 405 × 516 mm (W×D×H)

#### HEATER

Iron-chrome wire (Kanthal AF), 1.5 kW

#### WEIGHT

Approx. 30 kg

#### CLASS / TIER

Capital — high-temperature furnace / Tier 2

#### SAFETY DEVICES

Earth-leakage/circuit breaker, thermal fuse...

#### SETTING / DISPLAY

Digital setting; digital display

#### OPERATION FUNCTIONS

Fixed temperature; timer (auto-stop, auto-start); program...

#### TEMP RANGE

100 to 1150 °C

#### INTERNAL DIMENSIONS

100 × 250 × 150 mm (W×D×H)

#### SENSOR

R thermocouple (W sensor)

#### COOLING FAN

Axial fan motor

#### CONTROL SYSTEM

PID control by VS4 controller

#### MODEL / CAPACITY

Yamato FO200 (FO-211CR, comm-port gen) — approx. 3.75 L

#### ADJUSTMENT ACCURACY

$\pm 2$  °C (at 1150 °C)

#### ADDITIONAL FUNCTIONS

Lock function; auto recovery after power failure...

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours

