



LLS QUICK VIEW · YAMATO SCIENTIFIC

Refrigerated Incubator Programmable 143 L, Window + Shaker Hook-Up , 115V

SKU IN-604W-115V · Thermal Processing · Forced Convection Incubators

The Yamato IN-604W-115V is the window-and-shaker configuration of the IN604 programmable refrigerated incubator — the same 143 L stainless chamber



TECHNICAL SPECIFICATIONS

VOLTAGE

115V, 50/60 Hz (base spec sheet: AC100V, 13 A, 15 A...

EXTERNAL DIMENSIONS

710 × 645 × 913 mm (W×D×H)

DEFROST

Manual ON / automatic OFF, cycle operation

HEATER

Iron-chrome, 550 W

WEIGHT

Approx. 93 kg (base chamber)

COOLING MEDIUM

R134a, 310 ±5 g

REFRIGERATOR

Air-cooled full-closed reciprocating compressor, 250 W

OPERATION MODES

Fixed temp, auto-start, auto-stop, program (32 steps...

TEMP RANGE

-5°C to +50°C

INTERNAL DIMENSIONS

600 × 477 × 500 mm (W×D×H)

SHELVES

Stainless punching-metal; 15 kg/shelf; 30 mm bracket pitch

SENSOR

Platinum resistance bulb (Pt100Ω)

CABLE PORT

Inner diameter 30 mm (right side)

CLASS / TIER

Capital — refrigerated instrument / Tier 2

CONTROL SYSTEM

PID by microcomputer; programmable, 32 steps

MODEL / CAPACITY

Yamato IN604 (W config) — 143 L

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours

