



LLS QUICK VIEW · YAMATO SCIENTIFIC

## Refrigerated Incubator Programmable 286 L, Window , 220V

SKU IN-804W-220V · Thermal Processing · Forced Convection Incubators

The Yamato IN-804W-220V is the window configuration of the IN804 programmable refrigerated incubator — the same 286 L stainless chamber holding -5 °C



### TECHNICAL SPECIFICATIONS

#### VOLTAGE

220V, 50/60 Hz (base spec sheet rated AC100V; 220V per...

#### EXTERNAL DIMENSIONS

710 × 645 × 1630 mm (W×D×H)

#### DEFROST

Manual ON / automatic OFF, cycle operation

#### HEATER

Iron-chrome, 750 W

#### WEIGHT

Approx. 120 kg (base chamber)

#### COOLING MEDIUM

R404A, 260 ±5 g

#### REFRIGERATOR

Air-cooled full-closed reciprocating compressor, 300 W

#### OPERATION MODES

Fixed temp, auto-start, auto-stop, program (32 steps...

#### TEMP RANGE

-5°C to +50°C

#### INTERNAL DIMENSIONS

600 × 477 × 1000 mm (W×D×H)

#### SHELVES

5 stainless punching-metal shelves; 15 kg/shelf; 23...

#### SENSOR

Platinum resistance bulb (Pt100Ω)

#### CABLE PORT

Inner diameter 30 mm (right side)

#### CLASS / TIER

Capital — refrigerated instrument / Tier 1

#### CONTROL SYSTEM

PID by microcomputer; programmable, 32 steps

#### MODEL / CAPACITY

Yamato IN804 (W config) — 286 L

Distributed by Legacy Lab Supplies

legacylabsupplies.com · (855) 746-7557 / 855-SHOP-LLS · quotes in 24 hours

